

**GENERAL ELECTRIC COMPANY CAR CABLES FOR  
CONDUIT INSTALLATION.**

**STANDARD STRAND**

Size B&S	No. Wires in Strand	C.M.	Bare Diam.	600 Volts		1500 Volts	
				Diam. over all.	Approx. Wt. per 100 ft.	Diam. over all.	Approx. Wt. per 100 ft.
14	7		.073"	.263"	4.2	.33"	6
7	7		.165"	.385"	12.	.45"	14
6	7		.184"	.404"	14.	.47"	17
5	7		.208"	.425"	17.	.49"	20
4	7		.232"	.462"	20.	.52"	23
3	7		.263"	.493"	25.	.55"	27
2	7		.292"	.523"	29.	.58"	33
1	19		.332"	.594"	38.	.62"	39
0	19		.375"	.637"	45.	.67"	47
2/0	19		.419"	.681"	53.	.71"	57
3/0	19		.470"	.732"	67.	.76"	69
4/0	19		.528"	.790"	82.	.82"	85
250000	37		.576"	.875"	98.	.90"	99

**EXTRA FLEXIBLE**

19/25	19	6080	.09"	.278"	5.1	.34"	8.1
800/25	800	256000	.67"	1.05"	111.	1.05"	111.
900/25	900	288000	.70"	1.08"	122.	1.08"	122.
1000/25	1000	320000	.715"	1.10"	133.	1.10"	133.
1250/25	1250	400000	.845"	1.23"	163.	1.23"	163.
1500/25	1500	480000	.90"	1.28"	191.	1.28"	191.

**BUS LINE JUMPER CABLES**

100/25	100	32000	.25"	.50"	19.6	.665"	25.
400/25	400	128000	.46"	.875"	64.9	.870"	66.
500/25	500	160000	.51"	.937"	77.	.915"	78.